(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 28 April 2005 (28.04.2005)

PCT

(10) International Publication Number WO 2005/037459 A1

(51) International Patent Classification⁷: 9/06, B21K 1/14, 1/18

B21J 5/08,

(21) International Application Number:

PCT/JP2004/015878

(22) International Filing Date: 20 October 2004 (20.10.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003-360934 60/513,990

21 October 2003 (21.10.2003) JP 27 October 2003 (27.10.2003) US

(71) Applicant (for all designated States except US): SHOWA DENKO K.K. [JP/JP]; 13-9, Shiba Daimon 1-chome, Minato-ku, Tokyo 105-8518 (JP).

(72) Inventors; and


(75) Inventors/Applicants (for US only): OTAKI, Atsushi [JP/JP]; c/o Oyama Regional Office, Showa Denko K.K.,

480, Inuzuka 1-chome, Oyama-shi, Tochigi 323-8678 (JP). HAMANO, Hidemitsu [JP/JP]; c/o Oyama Regional Office, Showa Denko K.K., 480, Inuzuka 1-chome, Oyama-shi, Tochigi 323-8678 (JP).

- (74) Agents: SHIMIZU, Hisayoshi et al.; Idemitsu Nagahori Bldg.,, 4-26, Minamisemba 3-chome, Chuo-ku, Osaka-shi, Osaka 542-0081 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: FORGING METHOD, FORGED ARTICLE AND FORGING APPARATUS



(57) Abstract: An axial intermediate portion of the raw material 5 is held with a holding die 10 in a state in which the intermediate portion is prevented from being enlarged in diameter. The axial end portions of the raw material 5 is inserted in forming dented portions 6 and 6 formed at axial end portions of the holding die 10. The scheduled diameter-enlarging portions 6 and 6 are inserted in insertion passages 22 formed in guides 20. Then, the scheduled diameter-enlarging portions 6 and 6 are simultaneously pressed with punches 30 to fill the material of the scheduled diameter-enlarging portions 6 and 6 in corresponding forming dented portion while moving each guide 20 in a direction opposite to a moving direction of each punch 30, thereby enlarging each scheduled diameter-enlarging portion 6.

WO 2005/037459 A1



FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

 before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.